



SHELL CHAIN AND BAR OIL

Quality lubricant for high performance chain and bar

Product Description

Shell Chain & Bar Oil 100 is formulated for use in all chain saw mechanical or automatic oiler systems used to lubricate the bar and chain. **Shell Chain & Bar Oil 100** is formulated with highly refined base stocks and an effective anti-wear additive agent to help reduce wear of the moving chain and bar guide. A special tackiness agent is also added which promotes adhesion to moving parts and helps minimize oil throw off. **Shell Chain & Bar Oil 100** is dyed red for ease of visibility on the bar and chain.

Applications

- chain saw mechanical parts
- automatic oilers systems for the chain and bar

Features/Benefits:

- reduced wear of bar and chain
- reduced oil throw off
- visual check of oil getting to bar and chain

Typical Properties of Shell Chain and Bar Oils

	Test Method	ISO Viscosity Grade
		100
Product Code		65546
Appearance		Red, Stringy
Gravity, °API	D 1298	28.0
Flash Point, COC, °F	D 92	300
Pour Point, °F	D 97	-20
Viscosity:		
@ 40°C, cSt	D 445	100
@ 100°C, cSt	D 445	10.0

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>