



# SHELL ENSIS<sup>®</sup> COMPOUND DW 1016

## Solvent based corrosion inhibitor

### Product Description

**Shell Ensis Compound DW 1016** is a solvent based rust inhibitor and is intended for use on component parts or finished assemblies and equipment. It provides up to two years indoor or six to nine months outdoor storage protection under typical conditions. **Shell Ensis Compound DW 1016** is used as received in dip, spray or fogging equipment where excellent displacement of water or alkaline fluid is required.

For all applications, this product is used directly from the drum as received. Surface films of this product are readily removed with typical industrial alkaline cleaners or by vapor degreasing. Before use, **Shell Ensis Compound DW 1016** should be agitated to provide even coatings.

### Applications

- dip, spray or fogging applications where excellent displacement from water or cleaners is required
- applications where up to two years of indoor protection or six to nine months outdoor protection is required

One gallon of **Shell Ensis Compound DW 1016** will cover approximately 1800-2200 sq. feet with a film thickness of about 1.5 to 2.5 mm.

### Features and Benefits

- long term protection helps to eliminate rework and keep scrap to a minimum
- soft waxy film prevents cracking and peeling of protective film
- low viscosity allows for easy application with dip or spray equipment
- quick drying time (typically less than an hour) avoids delays in putting parts in storage

---

### Typical Properties of Shell Ensis Compound DW 1016

	Test Method	
Product Code (drums)		5063378
Appearance	Visual	Dark brown liquid
Film Characteristics		Soft, waxy film
Flash Point, °F	D 92	170
Density, lbs/gal		6.78

### **Handling & Safety Information**

Store away from extreme temperatures. Keep drums and processing containers away from open flame. Airless sprayers should be used to minimize cost. For information on the safe handling and use of this product, refer to its Material Safety Data Sheet **<http://www.equivashellmsds.com>**. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.