



SHELL FENELLA[®] OIL DS 1000

Stamping lubricant

Product Description

Shell Fenella Oil DS 1000 is a light duty lubricant designed for those applications wherein minimal oil film is needed. Shell Fenella Oil DS 1000 should be used in stamping operations to keep the tools cool and prevent wear. Shell Fenella Oil DS 1000 is safe to use on a wide variety of metals.

Applications

- light duty drawing and stamping operations
- applied by spraying, dipping, brushing or roller coating methods

Caution should be taken when sprayed to not exceed the permissible exposure limits to oil mist.

Features and Benefits

- excellent cooling and lubricating properties helping to reduce wear and give excellent part finish
- low odor
- high flash point helping to reduce risk of fire
- low residue results in safer handling of parts

Typical Properties of Shell Fenella Oil DS 1000

| | Test Method | |
|----------------------|-------------|---------------------|
| Product Code (drums) | | 5064216 |
| Appearance | Visual | Clear yellow liquid |
| Viscosity, SUS | | 110 |
| Flash Point, °F | TCC? | 340 |

Handling and Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.equivashellmsda.com>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please call **1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.