

# FormulaShell™

## POWER STEERING FLUID

### POWER STEERING FLUID

**Helps Protect Power Steering Unit Components Against Wear**  
**Helps Prevent Rust and Corrosion**  
**Protect against seal and hose deterioration**

### PRODUCT DESCRIPTION

FormulaShell™ POWER STEERING FLUID is a premium quality fluid designed to provide high performance in power steering systems. It has been formulated to reduce power steering pump squeal even under severe conditions. FormulaShell™ POWER STEERING FLUID offers high performance for virtually all power steering systems (see Applications) including those specifying the use of automatic transmission fluids.

FormulaShell™ POWER STEERING FLUID helps prolong the life of power steering units. ATF is often used as Power Steering Fluid. Recommended for complete fluid replacement or top-off in most passenger cars and light duty trucks.

### NOT RECOMMENDED FOR USE IN HONDA VEHICLES

### APPLICATIONS

Meets the service requirements for:

- DaimlerChrysler MS5931
- Ford ESW-M2C128-C and D
- GM 9985010
- Volkswagen TL-VW-570-26
- Navistar TMS6810

Also suitable for use in Mazda, Mercedes-Benz, Subaru and Volvo:

Note: Do not use in power steering systems, which require Honda Part No. 08208-99961. The owner's service manual specifications should be followed for all applications.

### PRECAUTIONS

The petroleum hydrocarbons used in this product have been severely hydrotreated and/or solvent refined and are considered non-hazardous under current OSHA regulations. Good hygiene, which includes regular washing of skin with soap and water and frequent changing of soiled clothing, should be used to avoid possible skin irritation and/or dermatitis. The formation of mists should be avoided. If FormulaShell™ POWER STEERING FLUID contacts the eyes, flush with large amounts of fresh water for 15 minutes or until the irritation subsides.

### WARNING

“Empty” containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition; they may explode and cause injury or death. “Empty” drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

**TYPICAL PHYSICAL AND CHEMICAL PROPERTIES**  
**FormulaShell™ POWER STEERING FLUID**

<b>TEST</b>	<b>TYPICAL RESULTS</b>
API Gravity, 15.6°C (60°F)	29.5
Viscosity, cSt @ 40°C (SUS)	39.5
Viscosity, cSt @ 100°C (SUS)	7.9
Viscosity Index	177
Flash Point, COC, °C, (°F), Min.	178
Pour Point, °C, (°F), Max.	-42
Material Number 12/12 ounce	5120312112