



SHELL GEAR GREASES TM AND TM-H

Locomotive traction motor gear greases

Product Description

Shell Gear Greases TM and TM-H are lithium soap thickened gear lubricants containing extreme pressure additives. These products are especially suitable for the lubrication of railroad locomotive traction motor gears.

Application

Shell Gear Greases TM and TM-H are specifically designed to lubricate the traction motor gear cases of all locomotives including the newest, high horsepower per axle units.

These products should not be used to lubricate anti-friction bearings

Features

Shell Gear Grease TM-H is a lithium soap thickened traction motor gear lubricant using a high viscosity base oil blend and a sulfur/phosphorus extreme pressure agent. The Brookfield Apparent Viscosity (BAV) is in the range of 15,000-20,000 cP at 200°F. **Shell Gear Grease TM-H** is best used in situations where leakage is a major problem.

Shell Gear Grease TM is comparable to **Shell Gear Grease TM-H** but has a slightly lower BAV range of 5,000-10,000 cP at 200°F. The decrease in BAV can be attributed to a slightly lower lithium soap thickener content. **Shell TM Gear Grease** was developed for railroads preferring a lighter product than **Shell Gear Grease TM-H** and for cold weather operations.

Benefits

- long term and efficient gear protection against wear
- excellent lubrication for highly loaded gears
- ability to perform well under all types of conditions

Recommended for

- Traction motor gear cases of locomotives such as the 900 HP/axle EMD GP-50 and General Electric B-36 locomotives
- Electro-Motive Division of General Motors (EMD) under Specification EMS-1027.

Product Maintenance

The extremely tacky nature of **Shell Gear Greases TM and TM-H** necessitate the packaging of these products in sealed one-pound polyethylene bags. The sealed bags are to be added to the top opening of the traction motor gear case. Because the whole bag is added to the gear case, waste is minimized. Otherwise, normal handling procedures should be observed as with any petroleum based products.

Typical Properties for Shell Gear Greases TM and TM-H

	Test Method	TM-H	TM
Product Code		72525	72527
Appearance		-----Black-----	
Lithium Soap, wt%		1.8	1.5
Texture		----Semi-Fluid, Tacky----	
Brookfield Apparent Viscosity (BAV) 77°F No. 7 Spindle at 4 rpm, cP		500,000	300,000
200°F No. 3 Spindle at 4 rpm cP		17,500	7,500
Timken, OK Load, lbs	D 2509	40	40
Four-Ball EP	D 2596		
Load Wear Index, kgf		56	56
Weld Point, kgf		315	315

Handling Practices

For information on the safe handling and use of these products, refer to their Material Safety Data Sheets at <http://www.equivashellmsds.com>. For more information and availability, call **1+800-782-7852**.