



SHELL ONDINA[®] OIL

Premium quality lubricant for textile industry

Product Description

Shell Ondina[®] Oil 22 is a water-white oil blended from highly refined mineral oil. It is intended for use as a lubricant in the textile industry, as a slitter oil in the paper industry, or any other industry where oil may accidentally spill on fabric or paper and must not cause a stain.

Applications

- textile industry where machine oil staining is an issue
- lubricated twister rings
- sewing machine parts
- circular hosiery knitting machines
- double knitting machines
- slitter applications in the paper industry

Features/Benefits

- non-staining performance
- rust protection
- natural cleaning ability due to naphthenic base
- light viscosity

Typical Properties of Shell Ondina® Oil		
	Test Method	ISO Viscosity Grade
		22
Product Code		65544
Appearance		Water-White
Gravity, °API	D 1298	31.0
Flash Point, °F	D 92	335
Pour Point, °F	D 97	-25
Viscosity:		
@ 40°C, cSt	D 445	18.2
@ 100°C, cSt	D 445	3.7
@ 100 °F, SUS	(calc)	97
@ 210 °F, SUS	(calc)	39
Viscosity Index	D 2270	75

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call **1+800-468-6457** for all of your service needs. All other customers, please **call 1+800-840-5737** for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.